

# DOTY & SONS CONCRETE PRODUCTS, INC.

## CONCRETE PARKING BLOCKS

ALL BLOCKS USE EXTRA RICH SALT RESISTANT REINFORCED CONCRETE

AND HAVE A 20 YEAR PARKING BLOCK LIMITED WARRANTY\*\*



Call 1-800-233-3907 for Quantity Pricing

Standard Parking Block:	7' Long, 6" High x 10" Wide, 2 Anchoring Pegs, Weight 315 lbs. each.
Special Order Parking Block:	8' Long, 6 3/4" High x 10 1/2" Wide, 3 Anchoring Pegs, Weight 350 lbs. each.
Special Order Truck Parking Block:	8' Long, 10" High x 12" Wide, 3 Anchoring Pegs, Weight 680 lbs. each.

### Concrete Specifications:

Sand - washed torpedo sand. Stone - 3/8" washed pea gravel or 3/8" crushed limestone (if specified).

Cement – very light gray color: 7 – 7 1/2 bags per cubic yard. Water reducers used to increase strength and durability.

Chemically entrained air – 6-8% causes concrete to be more salt and chloride resistant.

Average strength after 28 days 5000 PSI Minimum. Concrete cured indoors under plastic cover before exposure to outside air.

Reinforcing: 7' Block: 2 pieces 3/8" #3 rebar. 8' Blocks: 2 pieces 1/2" #4 rebar. Reinforcing rebars held in center of block, evenly spaced. Used where needed to reinforce and strengthen Doty & Sons concrete parking blocks. Secondary reinforcing fiber is also used throughout the parking block to give it further strength.

<u>Hold Pegs:</u>	7' Long Parking Block:	Includes 2 ea. #4 (1/2") Grade 60 x 20" Long Pegs
	8' Long Parking Block:	Includes 3 ea. #5 (5/8") Grade 60 x 24" Long Pegs
	8' Truck Parking Block:	Includes 3 ea. #5(5/8") Grade 60 x 24" Long Pegs

**Doty & Sons Concrete Products, Inc.**  
1275 E. State Street, Sycamore, IL 60178  
Phone (815) 895-2884 or Toll Free (800) 233-3907  
Email: [info@dotyconcrete.com](mailto:info@dotyconcrete.com)

\*\*See Doty & Sons Parking Block  
Warranty Sheet for Details